

SCENICVIEW B17-2 CI Business Line TFT display – for comfortable working

Issue July 2006

Pages 2

The SCENICVIEW B17-2 CI combines perfect ergonomics and improved usability with an eye catching design for a reasonable price. With its consequently optimized ergonomic benefits and usability the SCENICVIEW Business Line displays are the ideal choice for intensive office use – improving efficiency and productivity. The highly flexible stand allows adjusting the display to a perfect ergonomic position with a minimum distance of only 75mm between the viewable area and the desk. Combined with the wide tilt range, this allows a natural and relaxed head position preventing neck tensions.

Based on DDC-CI (Display Data Channel – Command Interface) device the DisplayView™ IT Suite offers helpful software tools making the daily work more comfortable. DisplayView™ Manage makes the display ready for integration in Fujitsu Siemens Computers manageability concept.

With its integrated speakers and fast response time, the SCENICVIEW B17-2 CI is the ideal choice for modern PC applications.

Reliability

- Outstanding quality and stability
- Reliability of delivery
- Low power consumption
- Power management according to EPA

Usability

- Enhanced tilt-base with height-adjust
- Administrator is able to read inventory data
- DisplayView IT Suite included
 - DisplayView™ Click – comfortable adjust via mouse click
 - DisplayView™ Scale – for optimum legibility
 - DisplayView™ Surf – comfort for the internet
- DisplayView™ Manage – ready for manageability
- Space saving design
- Auto-adjust
- Integrated power supply
- Ease-of-use menu
- Plug & Play
- DVI-D and analog interface
- Standardised mounting interface
- Fast response time

Diversity

- Display portfolio for differentiated demands
- Meets highest demands in terms of office standards
- Comparable with 19-inch CRT display

Ergonomics

- Optimized ergonomic position close to desk adjustable
- Optimum flicker-free and distortion-free ergonomics
- Wide viewing angle
- High contrast and excellent focus
- Environmental friendly with low-radiation
- Immunity to external electromagnetic fields



Visible screen diagonal	17 inch (43 cm)	
Graphics display (dependent on graphics processor)		
Pixels	1280 x 1024 (recommended)	
Pixels *)	1024 x 768	
Pixels *)	800 x 600	
Pixels *)	640 x 480	
*) interpolated		
Text display (dependent on graphics processor)		
Pixels (max. 70 Hz)	720 x 400	
Picture size	338 x 270 mm	
Pixel Pitch	0.264 mm	
Frequencies		
Horizontal	30 - 82 kHz	
Vertical	56 - 76 Hz	
Brightness typical	300 cd/m ²	
Contrast typical	500 : 1	
Viewing angle typical	CR>5:1 *)	CR>10:1 **)
Horizontal	160°	140°
Vertical	150°	130°
Response time typical	8 ms	
Plug & Play	VESA DDC CI	
Ease-of-use menu		
Direct key access	auto adjust, mute, input select, OSD menu-lock	
Brightness / contrast	brightness, contrast, black level, auto level	
Image adjust	H, V position, clock, phase	
Audio	volume, mute	
Color	6500 K, 9300 K, native, customer settings	
OSD setup	language, position, timeout	
Advanced Information	factory recall display mode resolution notifier	
Tilt Base		
Tilt angle up to	-5° / +25°	
Height-adjust range	75 mm	
Audio characteristics		
Volume control	digital	
Audio signal input (from PC)	3.5 mm stereo phone jack	
Sound output	2.0 W (L) + 2.0 W (R)	

Electrical values	
Rated voltage	100 - 240 V
Frequency	50 - 60 Hz
Power draw typical	
Operating (w/o sound)	30 W
Power save mode	1 W
(Standby-, Suspend- and Off- mode)	
Soft switch off (front)	<1 W
Protection class	1
Temperatures / dimensions / weight	
Ambient temperature (to IEC721)	
Recommended range	15°C to 32°C
Limit	5°C to 35°C
Dimensions (lowest position)	
(H x W x D)	360 x 374 x 249 mm
Dimensions without base	
(H x W x D)	341 x 374 x 55 mm
Weight unpacked / packed	5.7 kg / 7.1 kg
without base unpacked	3.8 kg
Reliability typical	
MTBF (demonstrated)	70,000 h
Lifetime of LCD	50,000 h
(brightness > 50% of original brightness)	
Compliance with standards	
Product safety	EN60950
Ergonomics	GS mark ISO13406-2 (Pixel fault class II)
Radiation immunity and suppression	CE certification according RFI to EC Directive 89/336/EEC (EN55022/B, EN55024 EN61000-3-2/-3); TCO'03
Video input	
	1 x D-SUB analog 1 x DVI-D digital
Data cable (1.8 m)	
detachable on display	D-SUB (15-pin) analog DVI-D (24 pin) digital audio cable (1.8 m)
Power cable (1.8 m)	
	for wall socket Euro-Schuko-Type CEE7
Integrated power supply	
Plug type on display side	IEC-320-C13
Special features	
	Kensington Lock prepared, standardized mounting, interface according, VESA FPMPI (100mm) DisplayView™ software tools (Click, Scale, Surf)
Order code	
	S26361-K977-V152

